

MATERIAL SAFETY DATA SHEET	
MFG. BY: SAFE ENCASEMENT SYSTEMS EMERGENCY CONTACT: (800) 424-9300 ADDRESS: 4344 San Cascina Street Las Vegas, NV 89135 Revised: August 2008 Information. Phone: (888) 277-8834	SPECIAL FIRE FIGHTING PROCEDURES: For fires with this material, do not enter any enclosed or confined fire space without proper protective equipment, including self-contained breathing apparatus, to protect against the hazardous effects of normal products of combustion.
SECTION I - PRODUCT ID. PRODUCT NUMBER: SE-120 PRODUCT NAME: Protective-Skin PRODUCT CLASS: Acrylic Elastomeric Coating.	SECTION V - REACTIVITY DATA STABILITY: Stable. CONDITIONS TO AVOID: <i>Keep from freezing.</i> INCOMPATIBILITY (MATERIALS TO AVOID): None reasonably foreseeable. HAZARDOUS POLYMERIZATION: Will not occur HAZARDOUS DECOMPOSITION OR BY-PRODUCTS: Will not occur.
SECTION II - HAZARDOUS INGREDIENTS None known at a hazardous level. HMIS Hazard Rating = 0 0 0 J This product contains no heavy metals or fibers.	SECTION VI - HEALTH HAZARD DATA EFFECTS OF OVEREXPOSURE: INHALATION of excessive vapor/mist can cause headache, nausea and irritation of the nose, throat and lungs. EYE CONTACT: slightly irritating to eyes. SKIN EXPOSURE: irritating to skin upon Prolonged or repeated contact.
SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS APPEARANCE: Milky white liquid BOILING POINT: 100°C (212°F) SPECIFIC GRAVITY: 1.3 – 1.5 (H ₂ O = 1.0) VAPOR PRESSURE: (mm Hg @ 20°C) = 18 VAPOR DENSITY: lighter than 1.0 EVAPORATIVE RATE: less than 1.0 PERCENT VOLATILE (by volume): 40%	EMERGENCY AND FIRST AID PROCEDURES: For inhalation, move subject to fresh air. For eye contact, flush with large amounts of water for at least 15 minutes. See a physician if irritation persists. Wash effected skin area with soap and water. If swallowed, dilute by giving 2 glasses of water to drink and CALL A PHYSICIAN IMMEDIATELY. Never give anything by mouth to an unconscious subject. OTHER PRECAUTIONS: DO NOT TAKE INTERNALLY. KEEP AWAY FROM CHILDREN.
SECTION IV - FIRE & EXPLOSION HAZARD DATA FLAMMABILITY CLASSIFICATION: DOT - NOT REGULATED. FLASH POINT - N/A LEL - N/A EXTINGUISHING MEDIA: N/A UNUSUAL FIRE & EXPLOSION HAZARDS: Material can splatter above 212°F. Polymer film can burn.	SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE. STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Keep Spectators away. WEAR SKIN, EYE, AND RESPIRATORY PROTECTION DURING CLEANUP. Dike and contain with inert absorbent materials (sand, earth, etc.). Transfer to containers for recovery or disposal.
	Floors may be slippery, use care to avoid falls. Flush final traces with water. Keep spills and cleaning run-off materials out of municipal sewers or open bodies of water. WASTE DISPOSAL METHOD: Disposal should be in accordance with Federal, state and local regulations for water-based coatings. Coagulate the emulsion by the stepwise addition of ferric chloride and lime. Incinerate the solids and contaminated diking material at a permitted facility, according to Federal, State and local regulations. PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: <i>KEEP FROM FREEZING.</i>
	SECTION VIII - CONTROL MEASURES. VENTILATION: GENERAL VENTILATION IS RECOMMENDED DURING NORMAL USE. LOCAL VENTILATION MAY BE REQUIRED DURING CERTAIN OPERATIONS TO PREVENT INHALATION OF VAPORS. RESPIRATORY PROTECTION: Wear respirator (MSHA or NIOSH APPROVED or the equivalent) ORGANIC VAPOR/PARTICULATE RESPIRATOR. IN CASE OF POOR VENTILATION (or exposure to spray mist), USE NIOSH APPROVED ORGANIC VAPOR MASK. PROTECTIVE GLOVES: IMPERVIOUS GLOVES FOR PROLONGED OR REPEATED CONTACT. EYE PROTECTION: CHEMICAL SPLASH GOGGLES (ANSI 2-87.1) or EQUIVALENT. OTHER PROTECTIVE EQUIPMENT AND MEASURES: UNHINDERED ACCESS TO SAFETY SHOWER AND EYE WASH STATIONS. AS A GENERAL HYGIENIC PRACTICE, WASH HANDS AND FACE AFTER USE. Showers and cleaning of clothes are recommended. Use approved clothing when working around ACM or lead-based paints.
	SECTION IX - REGULATORY INFO. DOT PROPER SHIPPING NAME: Not Regulated. Follow all applicable OSHA and EPA regulations concerning normal latex spraying activities.