

Multipurpose Class ABC Dry Chemical Fire Extinguisher

Contains monoammonium phosphate dry chemical that is specially fluidized and siliconized. It chemically insulates Class A fires by melting at approximately 350°F. It smothers and breaks the chain reaction of Class B fires, and it is a nonconductor of electricity. Includes bar coded and bilingual labels for documenting extinguisher locations, inspections, maintenance and recharging. Meets ANSI standards and is UL and USCG approved with appropriate bracket. Temperature Range: -65° to 120°F. Additional UPS hazardous charge. Six-year warranty. Red.



Item No	UL Rating	Capacity	Discharge Time	Range	Bracket	Unit
Nozzle						
AMXB417	1A:10B:C	2½ lbs	10 Seconds	9-15'	Wall	Each
AMXB417T	1A:10B:C	2½ lbs	10 Seconds	9-15'	Vehicle/Marine	Each
Hose and Nozzle						
AMXB500	2A:10B:C	5 lbs	14 Seconds	12-18'	Wall	Each
AMXB500T	2A:10B:C	5 lbs	14 Seconds	12-18'	Vehicle/Marine	Each
AMXB456	4A:60B:C	10 lbs	20 Seconds	15-21'	Wall	Each
AMXA411	20A:60B:C	20 lbs	30 Seconds	15-21'	Wall	Each
Hose and Nozzle, Not FM Approved						
AMXB402	2A:10B:C	5 lbs	14 Seconds	12-18'	Wall	Each
AMXB402T	2A:10B:C	5 lbs	14 Seconds	12-18'	Vehicle/Marine	Each

Also available in Brass, Chrome Valves. Call customer service for ordering information.

Carbon Dioxide Aluminum Cylinder Fire Extinguisher

Discharges carbon dioxide as a white cloud of "snow" that smothers a fire by eliminating its oxygen. It is effective for Class B flammable liquid fires, and it is electrically nonconductive. Carbon dioxide is a clean, noncontaminating, odorless gas that is safe to use on clothing, equipment, valuable documents, or food. Extinguisher is dielectric with a nonmagnetic rustproof aluminum cylinder and discharge valve. Includes bar coded labels for documenting extinguisher locations, inspections, maintenance and recharging. Temperature Range: -40°F to 120°F. Five-year warranty. USCG approved with appropriate bracket. Meets ANSI and UL standards. FM approved.



Item No	UL Rating	Capacity	Discharge Time	Range	Bracket	Unit
With Horn						
AMX322	5B:C	5 lbs	10 Seconds	3-8'	Wall	Each
With Hose and Horn						
AMX330	10B:C	10 lbs	10 Seconds	3-8'	Wall	Each
AMX331	10B:C	15 lbs	12½ Seconds	3-8'	Wall	Each
AMX332	10B:C	20 lbs	19 Seconds	3-8'	Wall	Each

Halotron I Fire Extinguisher

Utilizes "Clean Agent" hydrochlorofluorocarbon (HCFC), a rapidly evaporating liquid that leaves no residue, to cool and smother Class A, B, and C fires. The dielectric Halotron I is pressurized with argon gas. Intended for use in areas with sensitive electronic equipment and ideal for boats and vehicles. Includes bar coded labels for documenting extinguisher locations, inspections, maintenance and recharging. USCG approved. Meets ANSI and UL standards. Temperature Range: -40°F to 120°F. Five-year warranty.



Item No	UL Rating	Capacity	Discharge Time	Range	Min. Space Req.	Bracket	Unit
Aluminum Valve, Nozzle							
AMXA384T	1B:C	1.4 lbs	9 Seconds	6-8'	196 Cubic Feet	Vehicle	Each
AMXB385TS	2B:C	5.25 lbs	9 Seconds	6-10'	350 Cubic Feet	Vehicle	Each
AMXB394TS	2B:C	5.25 lbs	9 Seconds	9-15'	770 Cubic Feet	Aircraft	Each
AMXB386T	5B:C	9 lbs	9 Seconds	9-15'	700 Cubic Feet	Vehicle	Each
Brass and Chrome-Plated Valve, Hose and Nozzle							
AMX397	1A:10B:C	22.5 lbs	9 Seconds	9-15'	1540 Cubic Feet	Wall	Each
AMX398	2A:10B:C	27.5 lbs	14 Seconds	12-18'	2170 Cubic Feet	Wall	Each

FIRE EXTINGUISHERS

Purple K Stored Pressure Fire Extinguisher

Siliconized potassium bicarbonate is extremely effective against Class B (combustible liquids such as gas and oil) fires. The Purple K has durable chrome-plated brass valves and an aluminum cylinder. It operates in a temperature range of -65°F to 120°F. UL, USCG listed and FM approved. Six-year warranty. Comes with a Vehicle Bracket for convenient extinguisher storage.



Item No	UL Rating	Capacity	Discharge Time	Range	Bracket	Unit
Fixed Nozzle						
AMXB410T	10B:C	2½ lbs	10 Seconds	9-15'	Vehicle-Marine	Each
Hose and Nozzle						
AMXB479T	30B:C	5 lbs	12 Seconds	12-18'	Vehicle-Marine	Each
AMXA413	120B:C	20 lbs	28 Seconds	15-21'	Vehicle-Marine	Each



125-lb ABC Dry Chemical Wheeled Fire Extinguisher (Nitrogen Cylinder Operated)



Used to effectively combat Class A (normal combustibles such as wood and cloth), Class B (combustible liquids such as gas and oil) or Class C (electrical) fires. A 23 cu. ft. nitrogen cylinder with a quick-opening valve pressurizes and completely discharges the agent cylinder, which contains 125 lbs of fluidized and siliconized monoammonium phosphate. 16 x 4" semi-pneumatic wheels allow for easy maneuvering. 50' hose lets the user move freely without having to move the heavy-duty steel cylinder. Operating temperature range is -65°F to 120°F. Features a 4" stainless steel fill opening, brass cap, and brass fittings. USCG approved.

Item No	UL Rating	Capacity	Discharge Time	Range	Wheels	Unit
AMX450	40A:240B:C	125 lbs	52 Seconds	30-40'	16 x 4"	Each



50- and 100-lb Carbon Dioxide Wheeled Fire Extinguishers



Carbon Dioxide smothers Class B (combustible liquids such as gas and oil) and Class C (electrical) fires. The full pneumatic wheels measure 16 x 4" and allow for easy portability of the large extinguisher. Features a quick opening "T" handle valve, and a horn-mounted shut-off valve. Available with one cylinder (50-lb) or two cylinders (100-lb). Operating temperature range of -40° to 120°F. USCG approved.

Item No	UL Rating	Capacity	Discharge Time	Range	Hose Length	Unit
AMX333	20B:C	50 lbs	44 Seconds	10-15'	15'	Each
AMX334	20B:C	100 lbs	74 Seconds	10-15'	40'	Each



Fire Extinguisher Wall Case

Protect expensive fire extinguishers from dust and harsh workplace environments. Wall case is made of corrosion-resistant, high-impact ABS. Bright red color makes case easy to find. Holds all major brands of extinguishers up to 30 lbs. Exterior: 20W x 13D x 32½"H. Interior: 18W x 10D x 28"H. Weight: 10 lbs. Red.

Item No	Description	Unit
ALL3100	Fire Extinguisher Wall Case	Each



THE MARCOM GROUP, LTD.

Fire Extinguisher Safety Meeting Kits™

Ensure that employees are informed about

proper fire extinguisher use, different classes of fires, and how to read fire extinguisher labels. Each **Safety Meeting Kit** includes:

- **DVD or VHS Program** that includes an 18-minute instructional video, schedule and attendance forms, an employee quiz and training certificates.
- **30 Booklets** that feature 16 illustrated pages that provide quick instruction of fire extinguisher use.
- **5 Posters** that measure 18 x 24" and reiterate important safety points.

Item No	Description	Unit
MGLK0000469EM	Using Fire Extinguishers Safety Meeting Kit (DVD)	Each
MGLK0000469EM	Using Fire Extinguishers Safety Meeting Kit (VHS)	Each
MGLV0000469EM	Using Fire Extinguishers DVD Program	Each
MGLV0000469EM	Using Fire Extinguishers VHS Program	Each
MGLB0000460EM	Using Fire Extinguishers Employee Booklets	Each
MGLP0000460EM	Using Fire Extinguishers Poster	Each



for your information

Don't see what you are looking for? Do you have questions? Please call us at 800.465.3898 or check out our website at www.safetyexpress.com.